


KV-2566AS / 2966AS

RM-827S

SERVICE MANUAL

Australian Model



KV-2566AS
Chassis No. SCC-D23K-A
KV-2966AS
Chassis No. SCC-D23J-A

GP-1A CHASSIS

MODELS OF THE SAME SERIES

KV-2566AS/2966AS	

SPECIFICATIONS

Power requirements 110 - 240 V AC, 50/60 Hz
Power consumption Indicted on the rear of the TV
Color system PAL, PAL60, NTSC_{3.58}, NTSC_{4.43}

Inputs

Antenna 75-ohm
VIDEO INPUT jacks: phono jacks
Video: 1 Vp-p, 75 ohms
Audio: 500 mVrms, high impedance
S-TERMINAL VIDEO INPUT jack:
4-pin DIN

Television system and Channel coverage

Television system	B/G
Low VHF band	E2 - E4
High VHF band	E5 - E12
UHF	E21 - E68
CATV	S01 - S03 S1 - S20

Outputs

VIDEO OUTPUT jacks: phono jacks
Video: 1 Vp-p, 75 ohms
Audio: 500 mVrms, high impedance

Audio output 5 W + 5 W
SUPER WOOFER speaker: 15 W

Model	KV-2566AS	2966AS
Picture tube Apporx. cm (inches)	64 (25)	72.4 (29)
Dimensions (w/h/d, mm)	689 x 513 x 494	782 x 577 x 515
Weight (kg)	35	47

Design and specifications are subject to change without notice.



TRINITRON® COLOUR TV
SONY®


TABLE OF CONTENTS

<u>Section</u>	<u>Title</u>	<u>Page</u>	<u>Section</u>	<u>Title</u>	<u>Page</u>
1. GENERAL			4. CIRCUIT ADJUSTMENTS		
1-1.	Antenna Connection	3	4-1.	A Board Adjustments	15
1-2.	Connecting the SUPER WOOFER	3	4-2.	F Board Adjustment	16
1-3.	Connecting a VTR or Other Equipment	3			
1-4.	Presetting TV Channels	5	5. DIAGRAMS		
1-5.	Watching the TV	5	5-1.	Block Diagrams (1)	17
1-6.	Watching the Video Input	5	5-2.	Block Diagrams (2)	19
1-7.	Adjusting the Picture and Sound	6	5-3.	Circuit Boards Location	23
1-8.	Using Convenient Features	7	5-4.	Printed Wiring Boards and Schematic Diagram	24
			• K Board	27	
2. DISASSEMBLY			• F Board	27	
2-1.	Rear Cover Removal	8	• AS Board	28	
2-2.	Service Position	8	• H Board	30	
2-3.	K Board Removal	9	• A Board	31	
2-4.	Picture Tube Removal	10	• V4 Board	38	
			• C Board	39	
3. SET-UP ADJUSTMENTS			5-5.	Semiconductors	41
3-1.	Beam Landing	11	6. EXPLODED VIEWS		
3-2.	Convergence	12	6-1.	Chassis	43
3-3.	Focus	14	6-2.	Picture Tube	44
3-4.	Screen (G2) and White Balance	14	6-3.	Speaker	45
			7. ELECTRICAL PARTS LIST		46

WARNING !!

AN ISOLATION TRANSFORMER SHOULD BE USED DURING ANY SERVICE TO AVOID POSSIBLE SHOCK HAZARD, BECAUSE OF LIVE CHASSIS. THE CHASSIS OF THIS RECEIVER IS DIRECTLY CONNECTED TO THE AC POWER LINE.

SAFETY-RELATED COMPONENT WARNING !!

COMPONENTS IDENTIFIED BY SHADING AND MARK  ON THE SCHEMATIC DIAGRAMS, EXPLODED VIEWS AND IN THE PARTS LIST ARE CRITICAL TO SAFE OPERATION. REPLACE THESE COMPONENTS WITH SONY PARTS WHOSE PART NUMBERS APPEAR AS SHOWN IN THIS MANUAL OR IN SUPPLEMENTS PUBLISHED BY SONY.

SECTION 1 GENERAL

The operating instructions mentioned here are partial abstracts from the Operating Instruction Manual. The page numbers of the Operating Instruction Manual remain as in the manual.

Operating Instructions


Before operating the TV, please read this manual thoroughly and retain it for future reference.

1-1. ANTENNA CONNECTION


To connect a VHF antenna or a combination VHF/UHF antenna - 75-ohm coaxial cable (round)

Plug the connector into the T socket of the TV.

(Rear)




1-2. CONNECTING THE SUPER WOOFER (EXCEPT for Model KV-2566AS)




1-3. CONNECTING A VTR OR OTHER EQUIPMENT

Connecting a VTR or Other Equipment Equipped with an S Video Output Jack




Connecting a VTR or Other Equipment not Equipped with an S Video Output Jack



Connecting a VTR or Camcorder to the VIDEO INPUT Jacks on the Front


This TV is equipped with 2 sets of VIDEO INPUT 2 jacks. 2 sets are not available to be used at the same time. When using equipment connected, turn off other equipment not in use. For connection, use a commercially available connecting cord.




Note

If you connect monaural equipment, connect the AUDIO output of the VTR to L (MONO) jack of VIDEO INPUT 2. The monaural sound will be heard from both speakers.

Connecting two VTRs for Tape Editing



Connecting an Audio System




Note

If you connect monaural equipment, connect the equipment to the L (MONO) jack. The monaural sound will be heard from both speakers.

1-4. PRESETTING TV CHANNELS

Presetting TV Channels Automatically


You can preset up to 30 channels automatically to the program position numbers (0 to 29) in numerical sequence from channel number 1.




1 Press the POWER button.



2 Press the PRESET ON/OFF button ①.



3 Press the AUTO PROGR button ②.



Manual Presetting

To change the program number for a channel, or to receive a channel of weak signal, preset the channel manually.

Example: To preset a channel in program number 8

1 Press the PRESET ON/OFF button.

2 Press the PROGR +/- buttons until "8" appears.

3 Press the TV SYSTEM button to select your TV system.

4 Press the MANUAL PROGR +/- buttons until the channel you want appears.

5 Press the PRESET ON/OFF button.

To preset other channels
Repeat steps 1 through 5.

Skipping Program Positions

You can skip the unused or undesired program position when you are selecting a program using PROGR +/- buttons.

Example: To skip program position 8

1 Press the PROGR +/- buttons until "8" appears.

2 Press the PRESET ON/OFF button.

3 Press the PIC MODE button on the Remote Commander.

4 Press the PRESET ON/OFF button.

To skip other channels
Repeat steps 1 through 3.

To cancel the skip setting
Preset a channel onto the position number, following the steps in "Presetting TV channels automatically" or "Presetting channels directly".

1-5. WATCHING THE TV

To switch on or off the TV

POWER

The TV power is turned on or turned off completely.

To select a channel

① ② ③
④ ⑤ ⑥
⑦ ⑧ ⑨
1- 0 2-

To select 8

To select 10

To select 25

or

PROGRAMPAGE

To adjust the volume

VOL

To set the TV to standby mode

MUTE
DISPLAY
TEXTURE

POWER

① ② ③
④ ⑤ ⑥
⑦ ⑧ ⑨

To turn on the TV, press the POWER button again or press the channel number buttons or the PROGR +/- buttons.

Note
You can also use the buttons on the TV that have the same function.

1-6. WATCHING THE VIDEO INPUT

1 Press the TV/VIDEO button on the Remote Commander.

2 Set the VTR to playback mode.


To return to TV mode
Press the TV/VIDEO button, the channel number buttons, or PROGR +/- buttons.

Note
Do not use the VTRs connected to the front and rear A/V connectors simultaneously. When you use a VTR, turn off or disconnect another VTR.

1-7. ADJUSTING THE PICTURE AND SOUND


Selecting the Picture Mode

Press the PIC MODE button.



Adjusting the Picture and Sound Quality


- 1 Select the adjustment item using SELECT button on the Remote Commander (for ANALOG SELECT button on the TV)
- 2 Adjust using the + and - buttons.



Note


If you change the PIC MODE setting after making the above adjustments, the adjustment changes according to the PIC MODE setting, and COL (color), BRI (brightness) and HUE return to their original factory settings.

To Set TV SYSTEM (Except for AS model)



If the sound is distorted or noisy, or color is abnormal while receiving a program through the VHF/UHF terminal, press the TV SYSTEM button until clear sound or normal color is obtained. This setting is retained in the program position.


To Set COLOR SYSTEM



Normally, set COLOR SYSTEM to AUTO.

If the color reproduction is abnormal (for example, the picture turns red or blue) while receiving PAL and PAL 60 playback signal, set to PAL. The picture color will become normal.

Adjusting SHARPNESS




Turn SHARPNESS clockwise to increase sharpness and counterclockwise to decrease sharpness.

1-8. USING CONVENIENT FEATURES


Turning On or Off the On-screen Display

Press the DISPLAY button.




Muting

Press the MUTE button.



Setting the Sleep Timer

The TV will be turned off after 30, 60, or 90 minutes.
Press the SLEEP button.




To cancel the sleep timer,
Press the SLEEP button until the sleep display disappears.

Setting a MUSIC SURROUND Mode

Set MUSIC SURROUND to ON during a stereo sound reproduction.
You receive a theatrical audio effect or live concert effect sound.
This function does not work for monaural sound.

Selecting the Sound (Stereo or Bilingual) You Want

Press the A/B/MTS button until you receive the sound you want.
The sound changes and the corresponding indicator lights up as shown in the following table.



Notes


- If the signal is very weak, the sound becomes monaural.
- If the stereo sound is noisy, select "regular" or "mono".
The sound becomes monaural and the noise will be reduced.

When receiving German system program


Broadcasting	Selected sound	
German Stereo	Sound (Indicator)	Stereo (A + B)
German bilingual	Sound (Indicator)	<div style="display: flex; align-items: center;"> <div style="text-align: center; margin-right: 10px;"> A (A) </div> <div style="text-align: center; margin-right: 10px;"> B (B) </div> <div style="text-align: center;"> A + B (A + B) </div> </div>

SECTION 2 DISASSEMBLY


2-1. REAR COVER REMOVAL




2-2. SERVICE POSITION



2-3. K BOARD REMOVAL




2-4. PICTURE TUBE REMOVAL



• REMOVAL OF ANODE-CAP


NOTE : Short circuit the anode of the picture tube and the anode cap to the metal chassis, CRT shield or carbon painted on the CRT, after removing the anode.

• REMOVING PROCEDURES



• HOW TO HANDLE AN ANODE-CAP

- ① Don't hurt the surface of anode-caps with sharp shaped material!
- ② Don't press the rubber hardly not to hurt inside of anode-caps!
A material fitting called as shatter-hook terminal is built in the rubber.
- ③ Don't turn the foot of rubber over hardly!
The shatter-hook terminal will stick out or hurt the rubber.



SECTION 3 SET-UP ADJUSTMENTS

- The following adjustments should be made when a complete realignment is required or a new picture tube is installed.
- These adjustments should be performed with rated power supply voltage unless otherwise noted.

The control and switch below should be set as follows unless otherwise noted :

PICTURE control..... normal

BRIGHTNESS control..... normal

Perform the adjustments in order as follows:

Preparations :

- Feed in the white pattern signal.
- Before starting degauss the entire screen.

3-1. BEAM LANDING

1. Input the white signal with the pattern generator.
Contrast } normal
Brightness }
2. Position neck ass'y as shown in Fig 3-2.
(29 inch only)
3. Set the pattern generator raster signal to red.
4. Move the deflection yoke to the rear and adjust with the purity control so that the red is at the center and the blue and the green take up equally sized areas on each side.
(See Fig. 3-1 through 3-3.)
5. Move the deflection yoke forward and adjust so that entire screen is red. (See Fig. 3-1.)
6. Switch the raster signal to blue, then to green and verify the condition.
7. When the position of the deflection yoke has been decided, fasten the deflection yoke with the screws.
8. If the beam does not land correctly in all the corners, use a magnet to adjust it.
(See Fig. 3-4.)




Fig. 3-1




Fig. 3-2




Fig. 3-3





Fig. 3-4

3-2. CONVERGENCE


Preparations :

- Before starting perform FOCUS, H.SIZE, V.LIN and V.SIZE adjustments.
- Set BRIGHTNESS control to minimum.
- Feed in dot pattern.


(1) Horizontal and Vertical Static Convergence




1. Adjust H.STAT VR to converge red , green and blue dots in the center of the screen. (Horizontal movement)
2. Adjust V.STAT magnet to converge red, green and blue dots in the center of the screen. (Vertical movement)
3. If the red, green and blue dots do not converge in the center of the screen with H.STAT VR, perform horizontal convergence adjustment using H.STAT VR and V.STAT magnet as shown below. (In this case, H.STAT VR and V.STAT magnet effect each other.)



- Tilt the V.STAT magnet and adjust static convergence to open or close the V.STAT magnet.



4. When the V.STAT magnet is moved in the direction of arrow ㉓ and ㉔, red, green and blue dots move as shown below.




If the blue dot do not Converge with red and green dots, perform following steps.


- HMC and VMC correction for BMC (Hexapole) Magnet.

1. HMC (Horizontal Miss Convergence) correction and motion of the Electron Beam with the BMC Magnet.

HMC correction (A)




HMC correction (B)




2. VMC (Vertical Miss Convergence) correction and motion of the Electron Beam with the BMC Magnet.

VMC correction (A)



VMC correction (B)



(2) Dynamic Convergence Adjustment

Preparations :


● Before starting perform Horizontal and Vertical static convergence Adjustmet.

1. Slightly loosen deflection yoke screw.
2. Remove deflection yoke spacers.



3. Move the deflection yoke for best convergence as shown below.

4. Tighten the deflection yoke screw.

5. Install the deflection yoke spacers.



(3) Screen -corner Convergence



3-3. FOCUS


Adjust FOCUS control for best picture.

3-4. SCREEN(G 2) and WHITE BALANCE {SCREEN(G2)}

1. Input dots pattern.
2. Set the PIC control at minimum and set the BRT control at maximum.
3. Confirm the BKG voltage is less than 180 Vdc when turning RV 706 (R.BKG), RV 704 (G.BKG) and RV 702 (B.BKG).
4. Note the color when becomes visible first when turning RV 708 (SCRN).


[WHITE BALANCE (Cut off)]

1. Input collar bar signl.
2. Set the PIC control to minimum and set the BRT control at normal.
3. Turn RV 703 (B.DRIVE) and RV 705 (G.DRIVE) fully clockwise.
4. Set RV 706 (R.BKG), RV 704 (G.BKG) and RV 702 (B.BKG) to minimum.
5. Turn RV 707 (SUB BRT) slowly to obtain a faintly visible blue stripe.
6. Switch over all white signal.
7. Adjust BKG controls for best white balance.
8. Set the PICTURE control to maximum. Observe the screen and adjust the DRIVE controls for best white balance.
9. Repeat steps 7 and 8.




SECTION 4 CIRCUIT ADJUSTMENTS

4-1. A BOARD ADJUSTMENTS



Channel display POSITION ADJUSTMENT (RV001)

1. Set PIC control to maximum.
2. Adjust RV001 so that the channel display should be positioned at up-right on the screen.



A • P • C ADJUSTMENT (CV443) (PAL)

1. Input the PAL color-bar signal.
2. Set the PIC, COL, and BRT controls to normal.
3. Short circuit between pin ④ and pin ④7 of IC301 with jumper.
4. Adjust CV443 for suitable color intensity.
5. Remove a jumper.

REF OSC 3.58 ADJUSTMENT (CV358) (NTSC 3.58)


1. Short circuit between pin ④ and pin ④7 of IC301 with a jumper.
2. Set the PIC, COL and BRT controls to normal.
3. Input NTSC 3.58 color-bar signal.
4. Adjust CV358 for suitable color intensity.
5. Remove the jumper.

ANTI PAL, LINE CRAWLING ADJUSTMENT (RV301, RV302, T301)


• ANTI PAL ADJUSTMENT

1. Input PAL color-bar signal.
2. Set the PIC, COL and BRT controls to normal.
3. Connect the oscilloscope to pin ③ of A-1 connector.
4. Adjust RV301 (DELAY) and RV302 (PHASE) to obtain the waveform as shown below.

• LINE CRAWLING ADJUSTMENT



1. Input the PAL color-bar signal.
2. Set the PIC, COL and BRT controls to normal.
3. Connect the oscilloscope to pin ③ of A-1 connector.
4. Adjust T301 for minimum line crawling.



RV822 PIN ANP (PINCUSHION AMPLIFIER)



RV823 PIN PHASE (PINCUSHION PHASE)



RV821 PIN COR (PINCUSHION CORRECT)



RV825 C.CORR(CORNER CORRECT)



RV824 H.SIZE (HORIZONTAL SIZE)




RV503 V.SIZE (VERTICAL SIZE)




RV502 V.LIN (VERTICAL LINEARITY)




CN550 H.CENT (HORIZONTAL CENTER)



RV551 V.CENT (VERTICAL CENTER)



4-2. F BOARD ADJUSTMENT




RF AGC ADJUSTMENT (IF1)

1. Receive a strong off-air signals.
2. Adjust RF AGC VR control so that snow noise and cross-modulation just disappear from the picture.

DIAGRAMS

CIRCUIT BOARDS LOCATION



Note:

- All capacitors are in μF unless otherwise noted. pF: μF 50WV or less are not indicated except for electrolytics.
- All resistors are in ohms.
- Δ : internal component.
- \square : nonflammable resistor.
- \square : adjustment for repair.
- Indication of resistance, which does not have one for rating electrical power, is as follows.

Pitch: 5mm
Rating electrical power: $\frac{1}{4}W$

Reference information

RESISTOR	: RN	METAL FILM
	: RC	SOLID
	: FPRD	NONFLAMMABLE CARBON
	: FUSE	NONFLAMMABLE FUSIBLE
	: RS	NONFLAMMABLE WIREWOUND
	: RB	NONFLAMMABLE CEMENT
COIL	: LF-8L	MICRO INDUCTOR
CAPACITOR	: TA	TANTALUM
	: PS	STYROL
	: PP	POLYPROPYLENE
	: PT	MYLAR
	: MPS	METALIZED POLYESTER
	: MPP	METALIZED POLYPROPYLENE
	: ALB	BIPOLAR
	: ALT	HIGH TEMPERATURE
	: ALR	HIGH RIPPLE

- All variable and adjustable resistors have characteristic curve B, unless otherwise noted.
- The components identified by \square in this basic schematic diagram have been carefully factory-selected for each set in order to satisfy regulations regarding X-ray radiation. Should replacement be required, replace only with the value originally used.
- When replacing components identified by \square , make the necessary adjustments indicated. If results do not meet the specified value, change the component identified by \square and repeat the adjustment until the specified value is achieved. (Refer to R872 adjustment on Page 12, 13.) When replacing the part in below table, be sure to perform the related adjustment.


(HOLD DOWN)

Part replaced (\square)	Adjustment (\square)
IC301, Q870, Q871, Q872, Q873, D870, D871, D872, C327, C328, C857, C861, C870, C871, C872, C873, C874, C875, R321, R323, R855, R856, R857, R870, R871, R872, R873, R874, R875, R876, R877, R878, R879, R880, R881, R884, HVR	R872


- Voltages are dc with respect to ground unless otherwise noted.
- All voltages are in V.
- Readings are taken with a 10M Ω digital multimeter.
- Readings are taken with a color-bar signal input.
- Voltage variations may be noted due to normal production tolerances.
- --- : B+ bus.
- The hold down check point is TP7 on the P Board.
- \rightarrow : signal path.
- \times : Selected to yield optimum performance.




Note: The components identified by shading and mark Δ are critical for safety. Replace only with part number specified.


SCHEMATIC DIAGRAM (1)



A BOARD WAVEFORM









Y/C, JUNGLE, H/V DEF
AF-OUT, MEMORY, BAND SW
μ-CONTROLLER, POWER

A

A



SCHEMATIC DIAGRAM (2)



C

[R, G, B OUT]

K

[ANT. AUDIO/
VIDEO INPUT]


P

[ABL DETECT. REF CONT]


PRINTED WIRING BOARD (2)

— CONDUCTOR SIDE —


— C BOARD —



— P BOARD —




— K BOARD —




5-5. SEMICONDUCTORS


CXA1213S



CXK5864BSP-10L



KEY-C00SV-F




LA7016




**LM393P
RC4558P
ST24C02AB1
TEA2031A**




LM1036N




L78LR05D-MA




**MC14052BCP
MC14049UBCP
TDA8444
μ PD4053BC**



**MC14086BCP
MC33079P**



**PCA84C84P/054
TC8011N**




RC78L09A




RC7812FA




STR-S5741




TA8662N




TDA2009A



TD6710AN




μ PC1498H



μ PC574J



μ PC7893HF




**DTA114ES
DTC114ES
DTC124ES
DTC143TS
DTC144ES
2SC3327-A**



**2SA1175-HFE
2SC2785-HFE**




**2SA1220A-P
2SC2611
2SC2688-LK**



**2SA1221-L
2SB734-34
2SC2958-L
2SD774-34**




**2SA1306A-Y
2SC3298B-Y**



2SC2216



2SC4927-01




2SD1408-Y



2SK669




D4SB60L-F



D5LC20U




EGP30GL-8072
ERC06-15S
RU-1P
RU-3AM



MC932




SEL1222R-C



RBV-406H-01



ERD29-08J
RU4DS



EU2Z
ES1F-N
R2K
WG713A




RD10ES-B2
RD10ES-B3
RD13ES-B2
RD13ES-B3
RD39ES-B2
RD5.1ES-B2
RD5.6ES-B2
RD6.2ES-B2
RD6.8ES-B3
RD7.5ES-B1
RD7.5ES-B3
RD9.1ES-B1
RD9.1ES-B2
RD9.1ES-B3
1SS119



MC911



RD10SB1



MC921



U05G



SECTION 6 EXPLODED VIEWS


NOTE:

- Items with no part number and no description are not stocked because they are seldom required for routine service.
- The construction parts of an assembled part are indicated with a collation number in the remark column.
- Items marked "★" are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.

The components identified by shading and mark **▲** are critical for safety.
Replace only with part number specified.

6-1. CHASSIS

- : BVTP 3 × 12 7-685-648-79
- : BVTP 4 × 16 7-685-663-79




REF.NO.	PART NO.	DESCRIPTION	REMARK	REF.NO.	PART NO.	DESCRIPTION	REMARK
1	*1-644-571-12	H BOARD		11	▲ 1-574-358-21	CORD, POWER (WITH CONNECTOR)	
2	*4-394-974-01	CASE (BOTTOM LID), SHIELD		12	4-319-520-11	SCREW, SPECIAL (+PW4X30)	
3	*A-1297-054-A	A BOARD, COMPLETE (KV-2566AS)		13	*1-557-056-31	CABLE, P-P	
	*A-1297-035-A	A BOARD, COMPLETE (KV-2966AS)		14	*1-555-400-00	CABLE, PIN	
4	▲ 1-463-848-11	TUNER, ET (BT-886A)		15	*A-1245-491-A	F BOARD, COMPLETE	
5	▲ 1-439-416-41	TRANSFORMER ASSY, FLYBACK (NX-1604)		16	*1-634-621-11	AS BOARD	
6	4-037-247-01	PUSH BUTTON		17	▲ 1-563-204-13	SOCKET, ANTENNA (PAL)	
7	X-4030-526-1	BUTTON ASSY, POWER	8	18	*A-1385-133-A	K BOARD, COMPLETE (KV-2566AS)	
8	4-864-307-00	RING			*A-1385-125-A	K BOARD, COMPLETE (KV-2966AS)	
9	*4-397-431-01	COVER, HOLDER, LED		19	4-038-219-01	COVER, REAR (KV-2566AS)	
10	▲ 4-389-778-01	HOLDER, AC CORD			4-037-257-01	COVER, REAR (KV-2966AS)	

KV-2566AS/2966AS

RM-827S

6-2. PICTURE TUBE

● : BVTP 3 × 12 7-685-648-79




The components identified by shading and mark Δ are critical for safety. Replace only with part number specified.

REF.NO.	PART NO.	DESCRIPTION	REMARK	REF.NO.	PART NO.	DESCRIPTION	REMARK
51	X-4030-784-1	CABINET ASSY (WITH BEZEL ASSY)	52-59 (KV-2566AS)	67	*A-1342-195-A	V4 BOARD, COMPLETE (KV-2966AS)	
	X-4030-608-5	CABINET ASSY (WITH BEZEL ASSY)	52-59 (KV-2966AS)	68	*A-1331-243-A	C BOARD, COMPLETE (KV-2566AS)	
52	4-038-254-01	GRILLE (L), SPEAKER (KV-2566AS)			*A-1331-073-A	C BOARD, COMPLETE (KV-2966AS)	
53	4-037-263-01	GRILLE (L), SPEAKER (KV-2966AS)		69	*4-379-167-01	COVER (MAIN), CV (KV-2566AS)	
54	4-392-036-01	CATCHER, PUSH			*4-390-911-01	COVER (MAIN), CV (KV-2966AS)	
55	X-4030-708-2	DOOR ASSY, CONTROL (KV-2566AS)		70	*4-379-160-01	COVER (REAR LID), CV (KV-2566AS)	
56	X-4030-528-8	DOOR ASSY, CONTROL (KV-2966AS)			*4-390-907-01	COVER (REAR LID), CV (KV-2966AS)	
57	4-032-761-01	SHAFT (S), DOOR		71	4-303-774-99	SPRING (KV-2566AS)	
58	*4-389-517-01	GUIDE (R), LIGHT			4-369-318-00	SPRING, TENSION (KV-2966AS)	
59	4-038-253-01	GRILLE (R), SPEAKER (KV-2566AS)		72	Δ 1-426-385-11	COIL, DEMAGNETIZATION (KV-2566AS)	
60	4-037-262-01	GRILLE (R), SPEAKER (KV-2966AS)			Δ 1-426-408-21	COIL, DEMAGNETIZATION (KV-2966AS)	
61	4-037-255-01	BUTTON, MULTI		73	4-372-556-11	SHEET, BLOTTING (KV-2566AS)	
62	4-037-253-21	PANEL, CONTROL			4-385-725-01	SHEET, BLOTTING (KV-2966AS)	
63	1-503-902-11	SPEAKER		74	*4-387-284-01	HOLDER, LEAD	
64	*4-379-189-01	CUSHION, SPEAKER		75	4-033-681-01	HOLDER, LEAD (KV-2966AS)	
65	4-379-192-01	SCREW, TAPPING, STEP		76	4-390-505-01	SCREW (7), TAPPING	
66	Δ 8-733-230-05	PICTURE TUBE (A59JWB11X) (KV-2566AS)		77	4-308-870-00	CLIP, LEAD WIRE	
	Δ 8-733-834-05	PICTURE TUBE (A68JYK11X) (KV-2966AS)		78	1-452-032-00	MAGNET, DISK; 10MM ϕ	
67	3-704-495-01	SPACER, DY		79	1-452-094-00	MAGNET, ROTATABLE DISK; 150MM ϕ	
68	Δ 1-451-311-31	DEFLECTION YOKE (Y25FXA) (KV-2566AS)		80	X-4309-608-0	PERMALOY ASSY, CONVERGENCE (KV-2566AS)	
69	Δ 1-451-313-31	DEFLECTION YOKE (Y29FXA) (KV-2966AS)			X-4387-214-1	PERMALOY ASSY, CORRECTION	
70	Δ 1-452-509-42	NECK ASSY, PICTURE TUBE (NA-308) (KV-2966AS)		81	3-701-007-00	BAND, BINDING	
				82	1-503-486-11	SPEAKER (PIEZOELECTRIC TWEETER) (KV-2966AS)	

6-3. SPEAKER

- : BVTP 3 × 12 7-685-648-79
- : BVTP 4 × 16 7-685-663-79
- : BVTP 4 × 12 7-685-661-14



REF.NO.	PART NO.	DESCRIPTION	REMARK	REF.NO.	PART NO.	DESCRIPTION	REMARK
101	*A-1500-412-A	BOX ASSY, SP (KV-2966AS)		102-106	104	1-575-109-11	CORD, CONNECTION (KV-2966AS)
102	X-4030-531-1	COVER ASSY, TOP (KV-2966AS)			105	4-037-240-11	STOPPER (KV-2966AS)
103	1-544-363-11	SPEAKER (10CM) (KV-2966AS)			106	4-037-244-01	FOOT (KV-2966AS)